

Marie Krutzfield, Recorder
 Jones County, Iowa

J.D. TJEPKES, LS. JONES COUNTY ENGINEER'S OFFICE, 19501 HWY. 64, ANAMOSA, IOWA, 52205 (319)462-3785

UNITED STATES PUBLIC LAND
 SURVEY CORNER CERTIFICATE

LAND SURVEY MONUMENTS SITUATED IN SECTION 26, TOWNSHIP 86
 NORTH, RANGE 4 WEST OF THE 5TH P.M., JONES COUNTY, IOWA

CORNERS TO BE INDEXED

CORNER SECTION TOWNSHIP RANGE
 E1/4 26 86N 4W

OFFICE FILE NO.
 86426o_102606.tif

FIELD NOTES:
 MISC BK 2006
 P 80
 6-27-2006

MONUMENTS:
 SURVEY DISK WOOD POST
 SURVEY DISK POWER POLE
 FRONT FACE 6"x6" CONCRETE POST
 SURVEY DISK END POST
 HO DRIVE #20516

STATE PLANE COORDINATE
 NAD 83 IOWA NORTH
 N 3555102.116
 E 5525952.306

NOTE: THE STATE PLANE COORDINATE AS INDICATED IS FOR CONVENIENCE ONLY. THE TIES AS SHOWN SHOULD BE USED TO REPLACE THE CORNER, IF DESTROYED

PREVIOUSLY RECORDED IN BOOK NA, PAGE NA
 MONUMENT DESCRIPTION AND HOW ESTABLISHED

PER OLD TIES IN JONES COUNTY ENGINEER'S OFFICE DATED 1940, FOUND 1" IRON PIN BURIED 24" BELOW PRESENT ROADTOP. SET 5/8"x24" REBAR W/CAP #14807 ALONG SIDE AND WITH TOP IN POSITION OF OLD PIN, BURIED 4". TIES AS INDICATED FOR E1/4 CORNER SECTION 26 T86N R4W.

CORNERS TO BE INDEXED

CORNER SECTION TOWNSHIP RANGE
 N1/4 26 86N 4W

OFFICE FILE NO.
 86426c_102606.tif

FIELD NOTES:
 MISC BK 2006
 P 79
 6-28-2006

MONUMENTS:
 FD STONE SET 5/8"x24" REBAR W/CAP #14807
 TOP CENTER CONCRETE POST
 JONES CO SIGN
 SURVEY DISK WOOD POST
 SURVEY DISK TOP STEEL POST

STATE PLANE COORDINATE
 NAD 83 IOWA NORTH
 N 3557702.16
 E 5523247.91

NOTE: THE STATE PLANE COORDINATE AS INDICATED IS FOR CONVENIENCE ONLY. THE TIES AS SHOWN SHOULD BE USED TO REPLACE THE CORNER, IF DESTROYED

PREVIOUSLY RECORDED IN BOOK NA, PAGE NA
 MONUMENT DESCRIPTION AND HOW ESTABLISHED

FOUND 7"x11"x12" LIMESTONE STANDING ON END, ON NORTH SIDE OF CONCRETE CORNER POST BURIED 12". RAISED STONE AND SET 5/8"x24" REBAR W/CAP #14807 ON SOUTH SIDE OF STONE. TIES AS INDICATED FOR N1/4 CORNER SECTION 26 T86N R4W

CORNERS TO BE INDEXED

CORNER SECTION TOWNSHIP RANGE
 NE COR 26 86N 4W

OFFICE FILE NO.
 86426e_102606.tif

FIELD NOTES:
 MISC BK 2006
 P 78
 6-24-2006

MONUMENTS:
 SET 5/8"x24" REBAR W/CAP #14807 BURIED 2"
 SURVEY DISK WOOD END POST
 SURVEY DISK WOOD BRACE POST
 CL 200th AVE

STATE PLANE COORDINATE
 NAD 83 IOWA NORTH
 N 3557761.10
 E 5525892.11

NOTE: THE STATE PLANE COORDINATE AS INDICATED IS FOR CONVENIENCE ONLY. THE TIES AS SHOWN SHOULD BE USED TO REPLACE THE CORNER, IF DESTROYED

PREVIOUSLY RECORDED IN BOOK NA, PAGE NA
 MONUMENT DESCRIPTION AND HOW ESTABLISHED

PER PHYSICAL EVIDENCE, CL ROAD AND EQUAL DISTANCE BETWEEN FOUND PIN AT E1/4 SEC 26 AND FOUND PIN AT E1/4 SEC 23 T86N R4W. SET 5/8"x24" REBAR W/CAP #14807 BURIED 2" BELOW PRESENT ROAD TOP. TIES AS INDICATED FOR NE CORNER SECTION 26 T86N R4W.

CORNERS TO BE INDEXED

CORNER SECTION TOWNSHIP RANGE
 SE COR 26 86N 4W

OFFICE FILE NO.
 86435e_102606.tif

FIELD NOTES:
 MISC BK 2006
 P 78
 6-24-2006

MONUMENTS:
 SET 5/8"x12" REBAR W/CAP #14807 FLUSH WITH TOP OF ASPHALT
 "X" CUT TOP CONCRETE HEADWALL
 CL 200th AVE
 CL E-16

PREVIOUSLY RECORDED IN BOOK NA, PAGE NA
 MONUMENT DESCRIPTION AND HOW ESTABLISHED


PER TIES ON FILE AT JONES COUNTY ENGINEER'S OFFICE FROM PROJECT LC-2756(1) DATED 1969, SET 5/8"x12" REBAR W/CAP #14807 FLUSH WITH TOP OF PRESENT ASPHALT. TIES AS INDICATED FOR SOUTHEAST CORNER SECTION 26 T86N R4W

I hereby declare that this plat, survey or report was made by me or under my direct personal supervision and that I am a duly registered Land Surveyor under the laws of the State of Iowa.

Signed: *[Signature]* 10-27-06

Joseph D. Tjepkes L.S. Iowa Reg. No. 14807
 My Registration Renewal Date is December 31, 2006

SEAL



J.D. TJEPKES LS 14807
 JONES COUNTY
 ENGINEER'S OFFICE

19501 HWY. 64,
 ANAMOSA, IOWA,
 52205 (319)462-3785